

Horizontal Slider Model 100/140 2 3/4" Frame Depth



FEATURES

- C60, HC40, HC65
- Custom Sizes in Any Quantities
- Thermally broken main frame and vents
- Automatic Lock at Meeting Rail
- Adjustable stainless steel ball bearing rollers and stainless steel tracks
- Telescoped head and sill at jamb juncture
- Meeting rails are connected to frame without exposed fasteners
- Corner construction utilizes three assembly screws and gasket to ensure a watertight mainframe
- Exclusive Monoframe design for windows with transom, fixed lower panel or louvers
- Available for 1/4" monolithic or 3/4" insulating glass
- Operable sash lifts out for easy cleaning
- Semi-concealed meeting rail lock engages when closed
- 7/16" screen frame with charcoal-colored fiberglass mesh over operable vents
- Screen can be installed from the inside without removing the operable vent
- Hurricane Impact Tested



OPTIONS

- Model 140 rated AW80
- Class 1 Clear or Dark Bronze Anodized finish
- Duracron baked enamel white and bronze (0603.8)
- Custom Colors (Large Orders Only)
- Sash limit locks
- Locks for Handicapped Operation
- Flange frame
- 1 1/2" Slide on snap-fit offset nailing fin
- Available factory glazed or KD
- 6 psf., 10psf. or 15psf. water sill
- Receptor System
- 7/8" Insulated Laminated Large Missile Impact Glass (Dade Co. Tested)