

Sliding Glass Door

Model 200/250

5 1/2" Frame Depth



FEATURES

- AAMA rated HC40, HC50, HC75, HC80
- Custom Sizes in any quantities
- Thermally broken main frame and panel
- Thermal Rating CRF 51 and U-Value .62
- 5 1/2" Main frame
- No exposed fasteners
- Operable panel stiles are tubular
- Operable panel utilizes telescoped corners for additional strength
- Stainless steel roller track cover
- Tandem Rollers
- Mortice locks with four way adjustments
- ARLOC weatherstrip for tight air seal and low operating force
- Decorative interior handle and outside pull
- Tape glazing with interior EPDM wedge spline
- Available for 1/4" monolithic or 1" insulating glass
- 6 psf. Watersill
- Hurricane Tested



OPTIONS

- Model 250 Rated HC150
- Class 1 Clear or Dark Bronze Anodized finish
- Duracron baked enamel white and bronze (0603.8)
- Custom colors (Large Orders Only)
- Stainless steel Tandem rollers
- Stainless Steel Mortice Lock
- Available factory glazed or KD
- 6 psf, 10 psf. or 15 psf. watersill
- Deluxe extruded aluminum sliding screen door
- Receptor system
- 1" Insulated Laminated Large Missile Impact Glass (Dade Co, Tested)